

HPC X78II



Removable
Long-lasting Battery



Rugged Design
(1.2m Drop Test
IP65 Whole Unit)



Honeywell High Speed
2D Scanner#



Vehicle Mounting Capable#

Optional

SENIOR



SPECIFICATIONS

HPC X78II

PROCESSOR	ARM Cortex Quad-Core A73 2.0 GHz + Quad-Core A53 2.0 GHz
SYSTEM MEMORY	4 GB LPDDR4
STORAGE	64 GB eMMC

DISPLAY

SIZE / RESOLUTION	8" TFT LCD / 1280 x 800 pixels
BRIGHTNESS	400 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (5-point)

I/O INTERFACE

USB PORT	1 x Micro USB 2.0 (OTG Compatible)
SD SLOT	1 x Micro SD card slot (up to 512 GB)
SIM CARD	2 x Micro SIM
WI-FI & BLUETOOTH	Integrated IEEE 802.11 a/b/g/n/ac, Bluetooth 5.0
NFC	ISO/IEC 14443 Type A and B, FeliCa
WWAN	4G TDD-LTE/FDD-LTE, HSPA+/WCDMA

OPERATING SYSTEM

ANDROID	Android 11
----------------	------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	147 (W) x 220 (H) x 21 (D) mm 650 g
BATTERY	Replaceable 6200 mAh (up to 8 hours operating time)
CAMERAS	Front: 8.0 MP Rear: 13 MP (with flash)
SENSORS	GPS, ambient light sensor, E-Compass, G-Sensor (accelerate), Gyroscope, barometer
IP RATING	IP65 whole unit
DROP TEST	MIL-STD-810G compliant, 1.2 m drop resistance
TEMPERATURE	Operating: -10°C to 55°C Storage: -20°C to 65°C
HUMIDITY	Operating: 5% to 95% RH
ADAPTER INPUT	AC 100-240 V, 50/60 Hz
ADAPTER OUTPUT	DC 5V-2A, 9V-2A

MODEL OPTIONS

BARCODE READER	Honeywell N3603 barcode reader (1D/2D compatible)
DESKTOP CRADLE	227 (W) x 264 (H) x 180 (D) mm 690 g
VEHICLE DOCK	V-Dock with cigarette lighter power adaptor

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.