

K5POS



40 mm



40 mm Slim Chassis
Fully Aluminum Die-cast Unit



VESA Mount Capable



Easy Access SSD



IP66 Whole Unit
(Front & Back)

SEVOR



SPECIFICATIONS

	K5POS J64	K5POS N315
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Intel Core i3-N305 1.8 GHz (Turbo Boost up to 3.8 GHz)
SYSTEM MEMORY	1 x 8 GB DDR4 (supports up to 32 GB)	1 x 8 GB DDR4 (supports up to 16 GB)
STORAGE	1 x 128 GB removable M.2 PCIe 2280 SSD	

DISPLAY

SIZE / RESOLUTION	15" TFT LCD (LED backlight) / 1024 X 768 pixels
BRIGHTNESS	350 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	4 x USB 2.0, 2 x USB 3.0
SERIAL PORT	3 x RJ50 (DB9 adaptor included, DC 5V / 12V jumper selectable)
AUDIO PORT	2 x 2 W speaker, 1 x mic-in / line-out (combined)
VIDEO PORT	1 x HDMI
NETWORK PORT	1 x RJ45 10/100/1000 Mbps
CASH DRAWER PORT	1 x RJ12 (24 V by default, optional 12 V by jumper)

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro
---------	-----------------------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	366 (W) x 302 (H) x 159 (D) mm 6.0 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing with Nano-technology coating
VESA PATTERN	100 x 100 mm
IP RATING	IP66 whole unit
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C
HUMIDITY	10% to 90% (non-condensing)
POWER CONSUMPTION	12 V / 5 A, external power adaptor, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED CARD READER	3-track MSR, RFID (125 kHz / 13.56 MHz)
CUSTOMER DISPLAY	9.7"/15" TFT LCD or 2-line VFD
BARCODE READER	Tilt angle adjustable 1D / 2D barcode scanner

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.