KDS 21 **Kiosk Display System**














VESA Mount Capable*



Internal Power Supply Concealed Ports











SPECIFICATIONS	KDS J64	KDS T321
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Intel Dual Core i3-1215U 1.2 GHz (Turbo Boost up to 4.4 GHz)
SYSTEM MEMORY	1 x 8GB DDR4 RAM (up to 16 GB)	1 x 8GB DDR4 RAM (up to 32 GB)
STORAGE	1 x removable M.2 PCIe 2280 SSD	
DISPLAY		
SIZE	21.5" TFT LCD (LED backlight)	
RESOLUTION	1920 x 1080 pixels	
BRIGHTNESS	250 cd/m ²	
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)	
I/O INTERFACE		
USB PORT	3 x USB 2.0, 1 x USB 3.0	
SERIAL PORT	2 x RJ50	
NETWORK PORT	1 x RJ45 10/100/1000 Mbps	
CASH DRAWER PORT	1 x RJ12 (supports both 12 V & 24 V)	
VIDEO & AUDIO PORT	1 x HDMI	
SPEAKER	2 x 2 W	
OPERATING SYSTEM		
WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro	
ENVIRONMENT & MECHANICAL SPEC	IFICATIONS	
DIMENSIONS & WEIGHT	519 (W) x 322 (H) x 46 (D) mm 8.0 kg	
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing	
VESA PATTERN	100 x 100 mm	
SAFETY CERTIFICATION & IP RATING	IP66 compliant	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C	
HUMIDITY	Relative: 10% to 90% (non-condensing)	
POWER CONSUMPTION	DC output: 19 V / 3.42 A 65 W AC input: 100 V to 240 V	
MODEL OPTIONS		
INTEGRATED CARD READERS	3-track MSR (Dual Head & Dual Directional)	
WIRELESS LAN	Integrated Wi-Fi 802.11 b/g/n/ac, Bluetooth 4.1	

The Senor Building

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 sales@senortech.com.au



Quality. Safety. Versatility.