

NanoPAD X



Built-in MSR &
Front Camera



Smart Dock*
with Integrated 2" Printer



1D/2D Scanner*



VESA Mount Capable#

* Optional # Mounting poles/brackets not included

SEVOR



SPECIFICATIONS

NanoPAD X

| | |
|---------------|--|
| PROCESSOR | Intel Quad Core Celeron N4120 1.1 GHz, up to 2.6 GHz |
| SYSTEM MEMORY | 4 GB LPDDR4 RAM |
| STORAGE | 64 GB eMMC |

DISPLAY

| | |
|--------------------|---|
| SIZE / RESOLUTION | 10.1" TFT LCD (LED backlight) / 1280 x 800 pixels |
| BRIGHTNESS | 350 cd/m ² |
| TOUCH SCREEN PANEL | Projected capacitive touch (10-point multi-touch) |

I/O INTERFACE

Tablet (Standard)

Smart Dock (Optional)

| | | |
|------------------|---|----------------------|
| USB PORT | On tablet: 1 x USB 3.0, 1 x micro USB On dock: 2 x USB 2.0 | 3 x USB 2.0 |
| SERIAL PORT | N/A | 2 x DB9 |
| VIDEO PORT | 1 x micro HDMI | N/A |
| CASH DRAWER PORT | N/A | 1 x RJ12 (24 V) |
| EXTERNAL STORAGE | 1 x micro SD card slot (max. 32 GB) | N/A |
| ETHERNET | N/A | 1 x RJ45 10/100 Mbps |
| WIRELESS LAN | Dual-band Wi-Fi 802.11 b/g/n 2.4/5 GHz & Bluetooth 4.1 | N/A |

OPERATING SYSTEM

| | |
|---------|-----------------|
| WINDOWS | 10 IoT / 10 Pro |
|---------|-----------------|

ENVIRONMENT & MECHANICAL SPECIFICATIONS

| | |
|---------------------|---|
| DIMENSIONS & WEIGHT | Tablet: 282 (W) x 198 (H) x 18 (D) mm 1.0 kg |
| | Charging dock: 151 (W) x 121 (H) x 92 (D) mm 0.3 kg |
| | Smart dock: 236 (W) x 150-370 (H) x 218 (D) mm 2.8 kg |
| BATTERY | 7.4 V, 5500 mAh (up to 7 hours of normal usage) |
| TEMPERATURE | Operating: 5°C to 40°C Storage: -20°C to 60°C |
| HUMIDITY | Operating: 10% to 90% (non-condensing) Storage: 10% to 90% (non-condensing) |
| POWER CONSUMPTION | 12 V / 2 A, external power adaptor, 100-240 V, 50/60 Hz |
| | 24 V / 3.75 A, external power adaptor, 100-240 V, 50/60 Hz |

MODEL OPTIONS

| | |
|--------------------|---|
| SMART DOCK | Height/angle adjustable with keylock, 3 x USB 2.0, 2 x DB9, 1 x DK, 1 x LAN |
| 4G MODULE | 4G LTE/WCDMA/GSM |
| BARCODE READER | 1D / 2D barcode scanner |
| INTEGRATED PRINTER | 2" thermal printer (57 x 50 mm paper roll) |
| RFID READER | Supports MIFARE-One & MIFARE CPU card (13.56 MHz) |
| VESA PATTERN | 75 x 75 mm / 100 x 100 mm |

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.