

Peta POS



Concealed IO Ports



Removable SSD#



VESA Mount Capable*



IP55 Rated

SEÑOR

* Mounting poles/brackets for VESA mount not included
Windows based



SPECIFICATIONS

Peta POS J621

Peta POS A521

PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Rockchip RK3568, Quad core Cortex-A55, up to 2.0 GHz
SYSTEM MEMORY	8 GB DDR4 SO-DIMM RAM (up to 16 GB)	4 GB DDR4
STORAGE	1 x 128 GB 2.5" removable SATA SSD	32 GB eMMC

DISPLAY

SIZE / RESOLUTION	21.5" TFT LCD / 1920 x 1080 pixels
BRIGHTNESS	250 cd/m ²
TOUCH SCREEN PANEL	True-flat projected capacitive touch (10-point, multi-touch)

I/O INTERFACE

USB PORT	2 x USB 2.0, 2 x USB 3.0	2 x USB 2.0, 2 x USB 3.0
SERIAL PORT	1 x RJ50 (DB9 adapter included, DC 5V / 12V jumper selectable)	N/A
NETWORK PORT	1 x RJ45 10/100/1000 Mbps, optional BT 4.2 5 GHz & 2.4 GHz Wi-Fi 802.11 b/g/n/ac	1 x 10/100/1000 Mbps, BT 4.2 5 GHz & 2.4 GHz Wi-Fi 802.11 b/g/n/ac
AUDIO PORT	2 x 2 W speaker	2 x 2 W speaker

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro	Android 11
---------	-----------------------------------	------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	536 (W) x 329 (H) x 54 (D) mm 6.2 kg	536 (W) x 329 (H) x 47 (D) mm 6.0 kg
VESA PATTERN	100 x 100 mm	100 x 100 mm
IP RATING	IP55 whole unit	
TEMPERATURE	Operating: 0°C to 35°C	Storage: -15°C to 60°C
HUMIDITY	Operating: 20% to 85% (non-condensing)	Storage: 20% to 85% (non-condensing)
POWER CONSUMPTION	DC output: 12 V / 5 A 60 W (max.) AC input: 100 V to 240 V	

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.