ISPOS WP





Integrated Thermal Printer



Internal Power Supply



Floor Stand with Signage Board*





SPECIFICATIONS	iSPOS 1200 WP	iSPOS T715 WP
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Intel Dual Core i7-1255U 1.7 GHz (Turbo Boost up to 4.7 GHz)
SYSTEM MEMORY	8 GB DDR4 RAM (up to 32 GB)	8 GB DDR4 RAM (up to 64 GB)
STORAGE DEVICE	1 x 128 GB removable M.2 NVMe 2280 SSD, 1 x 128 GB removable M.2 SATA 2280 SSD	
DISPLAY		
SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels 17" TFT LCD / 1280 x 1024 pixels	
BRIGHTNESS	350 cd/m ²	
TOUCH SCREEN PANEL	15": resistive touch / projected capacitive touch 17": resistive touch	
I/O INTERFACE		
USB PORT	Front: 1 x USB 3.0 Back: 2 x USB 2.0 (up to 2 x USB 2.0 + 2 x USB 3.0)	
SERIAL PORT	2 x DB9 (up to 3 x DB9)	
AUDIO PORT	2 x built-in speakers 1 x 3.5 mm mic-in / line-out	
CASH DRAWER PORT	1 x RJ12 (24 V)	
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps	
OPERATING SYSTEM		
WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro	
ENVIRONMENT & MECHANICAL S	PECIFICATIONS	
DIMENSIONS & WEIGHT	15" iSPOS WP: 390 (W) x 470 (H) x 260 (D) mm 15 kg 17" iSPOS WP: 446 (W) x 520 (H) x 260 (D) mm 17 kg	
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing	
VESA PATTERN	75 x 75 mm / 100 x 100 mm	
IP RATING	IP66 on whole unit IP43 on printer with printer cover	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C	
HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)	
POWER CONSUMPTION	12 V / 5 A, internal power adaptor,100-240 V, 50/60 Hz	
MODEL OPTIONS		
INTEGRATED CARD READER	3-track MSR, RFID (supports 125 kHz/13.56 MHz (MIFARE)) Smart card reader, Fingerprint reader	
CUSTOMER DISPLAY	2-line VFD / 10" / 15" TFT LCD	
WIRELESS LAN	Integrated 802.11 b/g/n/ac + BT 5.0	
PRINTER COVER	Die-cast aluminium cover for TP-250	

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 sales@senortech.com.au



Quality. Safety. Versatility.